

## Specification

Loose lay printed acoustic floorcovering in tile format. Glass fibre reinforcement. TopClean XP™ Polyurethane reinforcement on surface.

CERTIFICATION & CLASSIFICATION	STANDARDS	iD Square
<b>Floor covering classification</b>	EN ISO 10874	Acoustic resilient floor covering Commercial very heavy: 34
<b>CE certification</b>	EN 14041	Yes
TECHNICAL CHARACTERISTICS	STANDARDS	iD Square
<b>Total thickness</b>	EN ISO 24346	4.5 mm
<b>Wear layer thickness</b>	EN ISO 24340	0.80 mm
<b>Total weight</b>	EN ISO 23997	5195 g/m <sup>2</sup>
<b>Wear layer binder content</b>	ISO 10582	Type I
<b>Form of delivery</b>	EN ISO 24342	
	Planks	25 x 100 cm 9 planks/box (= 2.25 m <sup>2</sup> - 12 kg) - 48 boxes/pallet
	Tiles	50 x 50 cm 9 tiles/box (= 2.25 m <sup>2</sup> - 12 kg) - 48 boxes/pallet  66 x 66 cm 5 tiles/box (= 2.22 m <sup>2</sup> - 12 kg) - 26 boxes/pallet
TECHNICAL PERFORMANCES	STANDARDS	iD Square
<b>Dimensional stability</b>	EN ISO 23999	≤ 0.10 %
<b>Reaction to fire</b>	EN 13501-1	B <sub>f1</sub> s1 loose-laid or glued over any A2 <sub>f1</sub> or A1 <sub>f1</sub> substrate (concrete) C <sub>f1</sub> s1 loose-laid or glued over any derivate wood substrate
<b>Residual indentation</b>	Average measured value EN ISO 24343-1 requirement	0.15 mm ≤ 0.20 mm
<b>Furniture leg</b>	EN 424	No damage
<b>Castor chair</b>	EN ISO 4918	No damage
<b>Thermal resistance</b>	ISO 10456	0.04 m <sup>2</sup> K/W
<b>Impact sound reduction</b>	EN ISO 717-2	ΔL <sub>w</sub> = 15 dB (±1 dB)
<b>Reduction of in room impact noise</b>	NFS S 31-074	Class B - L <sub>n,e,w</sub> = < 75 dB
<b>Acoustical absorption</b>	EN ISO 11654	α <sub>W</sub> = 0.05
<b>Light fastness</b>	EN ISO 105-B02	≥ 6
<b>Resistance to chemicals</b>	EN ISO 26987	High resistance
<b>Slip resistance</b>	EN 13893 DIN 51130	μ ≥ 0.30 R9
<b>Electrical properties</b>	EN 1081	R <sub>i</sub> > 10 <sup>10</sup> Ohm
<b>Colours</b>		41

Technical data in force upon the date of publication (11/15). The values correspond to laboratory tests (no in situ test) and are subject to modification. Tarkett's instructions regarding installation, cleaning and maintenance shall be observed. Please contact your local sales rep. for these instructions.

Our Sustainability tag explains the content of our products and how they contribute to our sustainability strategy and human well-being.

CUSTOMS TARIFF : 482050000000F

